

Nikon

NIKON SPEEDLIGHTS

SB-29s Macro Speedlight

TTL Macro Speedlight



- TTL Speedlight for Micro Nikkor and Select Lenses: Attaches to front of Micro Nikkor and Select Nikkor lenses for most convenient and accurate flash control
- Main Unit and Controller: Controller attaches to ISO hot shoe and Main Unit attaches to front of Micro Nikkor and Select Nikkor lenses
- ┘ Controlled Light Source: Two flash tubes provide extremely accurate TTL flash control during ultra close-up photography
- ┘ New Innovations: Main Unit can be attached to Controller on top of hot shoe, brightness of flash tubes can be reduced incrementally. Modeling light lets you check effects of flash before shooting. Manual power ratio of 1/4 or 1/32 power
- Aperture/Reproduction Ratio panel: Easy to read reproduction ratio scale on back of Controller is matched to Micro Nikkor lenses
- Multiple Flash capability: Extensive Nikon Multiple Flash System compatibility includes; SC-18 and SC-19 Cords and SU-4 Wireless Slave Flash Controller for TTL operation.

SB-29s Macro Speedlight

Two key concepts have driven Nikon flash innovations: automation and integration. The automation is found in Nikon's Matrix Balanced Fill-Flash, 3D Multi-Sensor Balanced Fill-Flash and multiple flash technologies. Integration is the seamless blending of flash capability with Nikon cameras' exposure systems. With Nikon Speedlights, you can capture the scene you see and the one you create in your mind's eye.

Speedlight Specifications:

Type of Speedlight:	Macro
Guide Number:	33 in feet at ISO 100
Flash Mode Selector:	TTL, 1/4 or 1/32 Power
Overexposure Warning:	Lights for approx. 4 seconds after shooting
Built-In Light Reducer:	Sets ratio of brightness of either right or left flash tube to 1/4 or 1/16 power
Modeling Illuminator:	Lights for approx. 3 seconds prior to taking photograph
Power Switch:	ON, OFF, Standby
Power Source:	Four AA Alkaline, Lithium, NiCd or NiMH batteries
Dimensions (W x H x D):	Approx. 2.3 X 3.3 X 1.4 inches
Weight:	Approx. 3.2 oz.
Product Number:	4719 NAS

For more complete specifications and compatibility information, refer to the SB-29s Speedlight instruction manual. Specifications and design are subject to change without any notice or obligation on the part of the manufacturer. 2/02

© 2002 Nikon Inc.

